

Properties

Description

Italian full grain, aniline dyed through leather. Available in 6 stock colours.

Attributes

Chrome tanned Bull hides, with a luxuriously velvety nap. Impregnated water repellency.

Hide Size

5.0m² / 54ft²

Thickness

1.3mm +/- 0.1mm

Weight

840gsm +/- 10g

Grain Characteristics

Natural

Finish Characteristics

Naked

Test Performance

Test	Test Method	Performance
Tear resistance	UNI EN ISO 3377-1	> = 20
Light Fastness	UNI EN ISO 105-B02	> = 3 / Blue Scale
Dry Rub Fastness - 50 cycles	UNI EN ISO 11640	> = 3 / Grey Scale
Dry Rub Fastness - 50 cycles - Evaluation on leather	UNI EN ISO 11640	> = 3 / Grey Scale

Flammability

Test	Test Method	Performance
Cigarette test - Match test	UNI EN 1021-1 - UNI EN 1021-2	Complies
Cigarette Ignition Resistance	NFPA 260/UFAC	Complies
FS191 Method 5903-Port Authority of New York & New Jersey		On demand
IMO Resolution A.652 (16)		Complies
California TB 117 Section E		Complies

Our leather is processed in conformity with REACH regulation.

Durability, Cleaning & Maintenance

Recommended for low to moderate traffic areas. This leather complies with the 3M test for oleo and hydro repellency. The Scotchgard treatment provides more protection and durability to the leather.

- Avoid placing leather in direct sunlight
- Keep the leather away from direct heat
- Dust regularly with a clean, soft, dry cloth

Certifications



UNI 11239



ISO 14025



ISO 14067/CD2



RAL-UZ 148